



# Floor Cleaning Brochure

## **CLEANING YOUR STONHARD FLOORS**

Stonhard's Stonkleen products are formulated to safely and effectively oxidize, degrease and remove stubborn stains inherent to your specific facility floors, while allowing the floors to retain their finish. This guide gives you step-by-step cleaning procedures. Instructions for each product are also located on product labels and on Product Data sheets. Also available to you are market-specific Floor Maintenance Sheets. You can find them at www.stonkleen.com or by calling your Stonhard representative.

#### **Benefits of Stonkleen products:**

- Safe, with environmentally sensitive options.
- Formulated to meet specific facility needs.
- Easy to use.
- Customized maintenance programs available.

### **Options For Cleaning Floors**

#### A Ride-On Floor Scrubber of any brand

• For very large areas.

#### An Advanced Convertamatic 24 Scrubber or equivalent

We recommend an easy-to-use model to minimize

the chance of damaging your floors.

- 20 gallon solution and recovery tanks.
- Optional on-board chemical system.
- For safety, flexibility and productivity, one touch scrubbing

and programmable controls.

- Soft nylon brush attachments always recommended. (White nylon brush attachment for most manufacturers.)
- Always start with the lightest brush pressure.

#### A Side-To-Side Floor Scrubber - 20-inch diameter

- Equipped with nylon brush head attachment (recommended).
- If used with degreasers, a secondary method will be needed for extraction and final rinse (e.g., shop vacuum or rubber squeegee).

#### **Manual Cleaning**

- Soft nylon deck or hand brushes.
- Used for spot cleaning, as well as corners and perimeter where scrubbers and side-to-side machines cannot reach.
- If deck brushes are used with degreasers, a secondary method will be needed for extraction and final rinse.



- Loose debris must be removed prior to using scrubbers.
- Equipment needs to be maintained and in good working order. This includes squeegees, brushes, wheels and working parts (mechanics) of the scrubber. Also, brushes should be inspected for foreign debris and wear.
- The floor surface should be wet (utilizing water dispensing) prior to engaging the machine's brushes. Starting the brushes on a dry floor may cause scratches and swirls in the floor.







## STONHARD

### RECOMMENDED MAINTENANCE SCHEDULE

#### **Daily Maintenance**

 Stonkleen DG2 - No rinse, green certified everyday cleaner. Can be used with a mop and bucket and also in a Ride-On or Walk-Behind floor scrubber.

#### Weekly Maintenance

- Stonkleen TD9 A heavy-duty degreaser and tire mark remover for industrial environments.
- Stonkleen FS9 A heavy-duty enzyme degreaser targeting fats, oils and organic compounds found in food service or food manufacturing environments.
- Proper dilution of both products are essential for maximum performance and economy.

#### Instructions:

For use in Ride-On and Walk-Behind floor scrubbers, if used with a Side-to-Side floor buffer, a secondary method of extraction will be needed. First pass with machinery is to be made with the vacuum and squeegee turned off. Allow product to penetrate 2 to 4 minutes. Second pass, scrub and extract using squeegee, and vacuum. Third pass with only clean water in the tank, scrub and extract using squeegee, and vacuum ensuring a thorough rinsing of the floor.

## DEEP CLEANING FOR HEALTHCARE ENVIRONMENTS

- Stonkleen AS9 Can be used to remove sanitizing and disinfecting films and residues that are left behind from health code protocols that, over time, will leave heavy build-up and dull the floor.
- Proper dilution of both products essential for maximum performance and economy.

#### Instructions:

For use in Ride-On and Walk-Behind floor scrubbers, if used with Side-to-Side buffer, a secondary method of extraction will be needed. Apply product to floor using mop and bucket. Allow to penetrate 2 to 4 minutes depending on the amount of residue or film. First pass with machine, scrub and extract using vacuum and squeegee. Second pass with only clean water in the tank, scrub and extract using squeegee, and vacuum ensuring a thorough rinsing of the floor.

## HEAVILY SOILED SPOT REMOVAL

- Stonkleen SR9 Used at full strength for removal of Betadine and other stubborn stains found in healthcare environments.
- Stonkleen TD9 At 50% dilution ratio with water, it is used for removal of tire marks from trucks, forklifts and pallet jacks. Also removes petrochemical stains.
- Stonkleen MD9 At 50% dilution ratio with water, it is used for food service areas and hard water mineral deposits.

#### Instructions:

Apply to stains, tire marks, and scuff marks. Allow product to penetrate 30 seconds to one minute, while scrubbing intermittently with soft nylon deck or hand brush. Extract with clean absorbent cloth or by mechanical means. Rinse thoroughly with clean water and wipe clean.

For your safety, all required personal protection equipment should be used when operating machinery or handling chemicals. For more information on customer specific maintenance programs, contact us at 866.505.7866 or visit us online at www.stonkleen.com.

## **STONHARD**



# **STONKLEEN PRODUCTS**

**Stonkleen FS9/Enzyme Degreaser** – Heavy-duty cleaner removes fats and oils found in food service/processing environments.

**Stonkleen MD9/Hard Water Cleaner** – Removes hard water mineral deposits found in food service/processing environments.

**Stonkleen TD9/Floor Cleaner for Tire Marks & Hard Residue** – Removes tire marks, petroleum oils and metal oxides found in manufacturing environments.

**Stonkleen SR9/Professional Spot Lifter** – Removes tough spots and stains, including grease, food and Betadine found in healthcare facilities.

**Stonkleen DG2/Green General Purpose Cleaner** – Green certified, no VOCs, effective daily cleaner for removing oils and greases found in public facilities.

**Stonkleen NC9/Neutral Floor Cleaner** – Used to efficiently clean and maintain acrylic finishes.

**Stonkleen AS9/Daily Floor Stripper** – A floor finish stripper/reliquifier designed to effectively remove aged, spray-buffed and multiple layers of floor finish.



